

DECLARATION OF PERFORMANCE
LE_0892510101_00_S_Silikondichtstoff Neutral

1. Unique identification code of the product type:

Silicone sealant acetate
Art. No. 0892510101

EN 15651-1:
EN 15651-2:
EN 15651-3:
EN 15651-4:

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade elements
EN 15651-1

Sealant used for sealing glazing applications
EN 15651-2

Sealant for joints in sanitary areas
EN 15651-3

Sealant for joints of pedestrian ways
EN 15651-4

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Würth International AG
Aspermontstrasse 1
CH – 7000 Chur

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 3 for testing fire behavior

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body IFT Rosenheim (0757) conducted the System 3 type test with respect to EN 15651-1 and for fire behavior and determined the following: test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

| Essential characteristics | Performance | Harmonised technical specification |
|--|------------------------------|--|
| Reaction to fire | Class E | EN - 15651-1-2012-12 EN - 15651-2-2012-12 EN - 15651-3-2012-12 EN - 15651-4-2012-12 |
| Release of chemicals harmful to health and/or the environment | Please see safety data sheet | |
| Elastic recovery | > 70% | |
| Resistance to flow | < 3mm | |
| Tensile properties - secant modulus | < 0,4 MPa | |
| Tensile properties at maintained extension | Passed | |
| Adhesion/cohesion at variable temperatures | Passed | |
| Adhesion-cohesion at maintained extension after water immersion | Passed | |
| Loss of volume (%) | < 10% | |
| Adhesion/cohesion after exposure to heat, water and artificial light | NF | |
| Microbiological growth: | 0 | |
| Tear resistance | Passed | |
| Durability | Passed | |
| Secant modulus | ≤ 0,9 MPa | |
| Tensile properties at maintained extension | Passed | |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG



Gerd Rössler
Managing Director

Chur, 30/06/2014



Patrick Kohler
Head of Power Tools/Material Processing