

DECLARATION OF PERFORMANCE

LE_0893212055_00_S_ Bitumen sealant

1. Unique identification code of the product type:

**Bitumen sealant 2K
Art. No. 0893212055
EN 15814 :2013-01: F-EXT-INT-CC
EN 15814-1**

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Polymer modified bituminous thick coatings for waterproofing
EN 15814-1**

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Würth International AG
Aspermontstrasse 1
CH – 7000 Chur**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3
System 3 for testing fire behavior**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body Testing institute high (1508) conducted the System 3 type test with respect to EN 15814-1 and for fire behavior and determined the following: test report

The notified body material examination Office Nordrhein-Westfalen (0432) conducted the System 3 type test with respect to EN 15814-1 and for fire behavior and determined the following: test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Water tightness and air tightness	Class W2A	EN 15814 :2013-01
Tear strength	Class CB2	
Resistance to water	No discoloration of the water, No repayment of the deposit	
Adhesion/ cohesion at maintained extension after cold	No cracks	
Adhesion/ cohesion at maintained extension after heat	No slipping and running	
Reaction to fire	Class E	
Compressive strength	Class C2A	
Release of chemicals dangerous to the environment and health	Component B: see MSDS	
Durability	passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG



Gerd Rössler
Managing Director



Patrick Kohler
Head of Power Tools/Material Processing

Chur, 10/06/2015