

DECLARATION OF PERFORMANCE

No. LE_0893311000_01_M_ACR 240

1. Unique identification code of the product:

Fire Resistant Acrylic ACR 240**Art. pre-number:****0893 311 000* , 0893 311 008***

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging

3. Intended use(s):

Product type	Fire stopping and fire sealing product
For use in	Penetration seals according to ETAG 026 Part 2
	Linear joint and gap seals according to ETAG 026 Part 3

4. Manufacturer as required pursuant to Article 11(5):

**Würth International AG
Aspermontstrasse 1
CH- 7000 Chur
Switzerland**

5. Authorized representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System(s) of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. a) When the construction product is covered by a harmonized standard:

not relevant

7. b) When the construction product is covered by a European Assessment Document:

ETAG 026 Part 2, 08/2011**ETAG 026 Part 3, 08/2011**

When 7b) applies

European Technical Assessment:

ETA 13/0989, 24/11/2014**ETA 13/0990, 24/11/2014**

Technical Assessment Body:

UL International (UK) Ltd

Notified Body:

UL International (UK) Ltd, Nr. 0843

8. Declared performance:


Essential characteristics	Measuring method	Performance	Harmonized technical specification
Reaction to fire	EN 13501-1	Class D-s1, d1	ETAG 026 Part 2 & ETAG 026 Part 3
Resistance to fire	EN 13501-2	Up to EI 240 depending on the application. See ETA 13/0989 & 13/0990	ETAG 026 Part 2 & ETAG 026 Part 3
Air permeability		no performance determined	
Water permeability		no performance determined	
Release of dangerous substances	declaration of manufacturer	no dangerous substances	ETAG 026 Part 2 & ETAG 026 Part 3
Mechanical resistance and stability		no performance determined	
Resistance to impact/movement		no performance determined	
Adhesion		no performance determined	
Airborne sound insulation	EN 10140-2 EN ISO 717-1	R _w (C; C _{tr})= 62 (-1; -5) dB (at 12 mm depth)	ETAG 026 Part 3
Thermal properties		no performance determined	
Water vapour permeability		no performance determined	
Durability and serviceability	EOTA TR 024: 2009	use category Z ₂	ETAG 026 Part 2 & ETAG 026 Part 3

9. When pursuant to Articles 37 and 38 appropriate technical documentation and/or Specific Technical Documentation has been used:


not relevant

The performance of the above product corresponds to the declared performance. The declaration of performance is issued in compliance with EU Regulation 305/2011 under the sole responsibility of the above manufacturer.

Signed for and on behalf of the manufacturer by:



Gerd Rössler
(Managing Director)
Chur, 07.10.2016



Patrick Kohler
(Head of Power Tools / Material Processing)