

DECLARATION OF PERFORMANCE
LE_0892520001_00_M_Neutralsilikon Spezial

1. Unique identification code of the product type:

Neutralsilikon Spezial
Art. No. 0892520001, 0892520002, 0892520011, 0892520012

EN 15651-1: F-EXT-INT-CC
EN 15651-2: G-CC
EN 15651-3: S-XS1

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Joint sealants for facade elements
EN 15651-1: F-EXT-INT-CC

Sealant used for sealing glazing applications
EN 15651-2: G-CC

Sealant for joints in sanitary areas
EN 15651-3: S-XS1

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Würth International AG
Aspermontstrasse 1
CH – 7000 Chur

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 3 for testing fire behavior

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body ZAG (1404) conducted the System 3 type test with respect to EN 15651-1 and for fire behavior and determined the following: test report

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Pre-Conditioning: Method A

Substrate: Aluminum without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1: 2012
Release of chemicals harmful to health and/or the environment	NPD	
Resistance to flow	≤ 3mm	
Loss of volume	≤ 10%	
Tensile properties (i.e. at maintained extension after immersion in water at 23 °C)	NF	
Tensile properties (i.e. secant modulus) for non-structural low modulus sealants used in joint in cold climate areas (-30 °C)	≤ 0.9 MPa	
Tensile properties (i.e. at maintained extension) for non-structural low modulus sealants used in joint in cold climate areas (-30 °C)	NF	
Durability	Passed	

Pre-Conditioning: Method A

Substrate: Aluminium without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-2: 2012
Release of chemicals harmful to health and/or the environment	NPD	
Vertical resistance to flow	≤ 3mm	
Loss of volume	≤ 10%	
Tensile properties (i.e. at maintained extension after immersion in water at 23 °C)	NF	
Elastic recovery	≥ 60%	
Tensile properties (i.e. secant modulus) at (-30±2 °C) for cold climate areas	≤ 0.9 MPa	
Tensile properties (i.e. at maintained extension) at (-30±2 °C) for cold climate areas	NF	
Durability	Passed	

Pre-Conditioning: Method A

Substrate: Aluminium without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-3: 2012
Release of chemicals harmful to health and/or the environment	NPD	
Resistance to flow	≤ 3mm	
Loss of volume	≤ 20%	
Adhesion/cohesion properties, i.e. elongation at maintained extension after immersion in water	NF	
Microbiological growth	1	
Durability	Passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG



Gerd Rössler
Managing Director

Chur, 03/03/2015



Patrick Kohler
Head of Power Tools/Material Processing