

## **DECLARATION OF PERFORMANCE**

**LE\_089322620\_00\_S\_Konstruktionsklebstoff MS Pool**

1. Unique identification code of the product type:

**Construction sealant MS Pool  
Art. No. 0893226200**

**EN 15651-1: F EXT-INT-CC  
EN 15651-3: S-XS3  
EN 15651-4: PW EXT-INT-CC**

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Joint sealants for facade elements  
EN 15651-1: F EXT-INT-CC**

**Sealant for joints in sanitary areas  
EN 15651-3: S-XS3**

**Sealant for joints of pedestrian ways  
EN 15651-4: PW EXT-INT-CC**

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Würth International AG  
Aspermontstrasse 1  
CH-7000 Chur**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3  
System 3 for testing fire behavior**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**The notified body ift Rosenheim GmbH (0757) conducted the System 3 type test for fire behavior and determined the following: test report**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant**

9. Declared performance:

Pre-Conditioning: Method B

Substrate: anodized aluminum and mortar M1

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	<b>EN 15651-1: 2012-12</b> <b>EN 15651-3: 2012-12</b> <b>EN 15651-4: 2012-12</b>
Release of chemicals harmful to health and/or the environment	Evaluated	
Resistance to flow	≤ 3mm	
Loss of volume	≤ 15%	
Tensile properties (i.e. stretch behavior) at maintained extensions after immersion in water	No failure	
Tensile properties at maintained extensions	No failure	
Tensile properties at maintained extension at -30°C	No failure	
Tensile properties (secant modulus/elongation at break)	No performance determined	
Tensile properties (secant modulus) at -30°C	No performance determined	
Adhesion/ cohesion at maintained extension after water immersion	No failure	
Adhesion/ cohesion at maintained extension after salt water immersion	No failure	
Microbiological growth	3	
Tear strength	No failure	
Durability	Passed	


Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG



Gerd Rössler  
Managing Director



Patrick Kohler  
Head of Power Tools/Material Processing

Chur, 28/05/2014