

# **DECLARATION OF PERFORMANCE**

LE\_0893220121\_01\_M\_IMPELAST\_RAPID\_FR\_EN

1. Unique identification code of the product type:

# IMPELAST\_RAPID\_FR N° de réf. 0893220121, 0893220122

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

#### batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

#### Liquid applied waterproofing

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

# Würth International AG Aspermontstrasse 1 CH-7000 Chur

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

#### Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

## System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

#### **MODENA CENTRO PROVE - No. 1599**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

#### Not relevant



## 9. Declared performance:

Essential characteristics	Performances	Harmonized standard
Initial tensile adhesion strength	≥ 0.5 MPa	EN 14891:2012
Tensile adhesion strength after heat ageing	≥ 0.5 MPa	EN 14891:2012
Tensile adhesion strength after water immersion	≥ 0.5 MPa	EN 14891:2012
Tensile adhesion strength after contact with lime water	≥ 0.5 MPa	EN 14891:2012
Tensile adhesion strength after freeze-thaw cycles	≥ 0.5 MPa	EN 14891:2012
Water impermeability	no penetration	EN 14891:2012
Crack bridging ability in standard conditions	≥ 0.75 mm	EN 14891:2012
Crack bridging ability at low temperatures (-5°C)	≥ 0.75 mm	EN 14891:2012
Release of dangerous substances	See MSDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG

Gerd Rössler Managing Director

Chur, 27/07/2018

Patrick Kohler

Head of Power Tools/Material Processing