

DECLARATION OF PERFORMANCE

LE_0893220006_01_S_WATERSTOP_FONDAMENTA_R

1. Unique identification code of the product type:

**WATERSTOP_FONDAMENTA_R
Art. 0893220006**

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Liquid applied waterproofing product. Revamping (c) for the surface protection of Concrete by protecting against penetration, controlling moisture and increasing resistivity.

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Würth International AG
Aspermontstrasse 1
CH-7000 Chur**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+ / 3 for reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 1504-2:2004

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Essential characteristics	Performances	Harmonized
Permeability to CO ₂	$S_0 > 50 \text{ m}$	EN 1504-2:2004
Water vapor permeability	CLASS I ($S_0 < 5 \text{ m}$)	EN 1504-2:2004
Capillary absorption and water permeability	$w < 0,1 \text{ Kg/m}^2 \cdot \text{h } 0,5$	EN 1504-2:2004
Bond strength by pull off test	$\geq 0,8 \text{ MPa}$	EN 1504-2:2004
Freeze-thaw cycling without de-icing salt immersion	$\geq 0,8 \text{ MPa}$	EN 1504-2:2004
Exposure to artificial atmospheric agents	No visible defects	EN 1504-2:2004
Crack bridging properties	Class A5 (23°C) Class A5 (0°C) Class A5 (-5°C)	EN 1504-2:2004
Reaction to fire	Euroclass E	EN 1504-2:2004
Release of dangerous substances	See MSDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG

Heiner Faust
Managing Director

Alexis Peñaloza
PM