

## **DECLARATION OF PERFORMANCE**

**LE\_089285732\_00\_M\_Silikon Neutral**

**This is an English translation of the original German wording.  
In cases of doubt, the German version applies**

1. Unique identification code of the product type:

**Silikon Neutral  
[Silicone Neutral]**

**Art. no. 089285732 - 089285733**

**EN 15651-1: F-INT-EXT-CC**

**EN 15651-2: G-CC**

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**batch number: see packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**joint sealants for facade elements  
EN 15651-1: F-INT-EXT-CC**

**joint sealant for glazing  
EN 15651-2: G-CC**

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Würth International AG  
Aspermontstrasse 1  
CH-7000 Chur**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3  
System 3 for testing fire behavior**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**The notified body SKZ – TeConA GmbH (1213) conducted the System 3 type test for fire behavior.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant**

9. Declared performance:

Conditioning: method B (in accordance with ISO 8340)

Base material: concrete M2, aluminum, and glass without primer

<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized technical specification</b>
Fire behavior (EN 13501)	Class E	<b>EN 15651-1: 2012</b>
Release of chemicals harmful to health and/or the environment	See safety data sheet	
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss in volume (ISO 10563)	≤ 10%	
Tensile properties (i.e. cohesion properties) at maintained extension and with immersion in water (ISO 10590)	No failure	
Tensile properties at maintained extension, at -30 °C (ISO 10590)	No failure	
Tensile properties (secant modulus) at -30 °C (ISO 8339)	≤ 0.9 MPa	
Durability (EN 15651)	Passed	

Conditioning: method B (in accordance with ISO 8340)

Base material: concrete M2, aluminum, and glass without primer

Essential characteristics	Performance	Harmonized technical specification
Fire behavior (EN 13501)	Class E	<b>EN 15651-2: 2012</b>
Release of chemicals harmful to health and/or the environment	See safety data sheet	
Resistance to flow (ISO 7390)	≤ 3 mm	
Loss in volume (ISO 10563)	≤ 10%	
Adhesion/cohesion properties at maintained extension after exposure to artificial light (ISO 11431 - preconditioning method B)	No failure	
Elastic recovery (ISO 7389)	≥ 60%	
Tensile properties at maintained extension, at -30 °C (ISO 8340)	No failure	
Tensile properties (secant modulus) at -30 °C (ISO 8339)	≤ 0.9 MPa	
Durability	Passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Würth International AG



Heiner Faust  
Managing Director

Chur, 05/11/2022



Leander Hein  
PM Chemicals