

DECLARATION OF PERFORMANCE

LE_0892211_00_M_Fassadendichtstoff

1. Unique identification code of the product-type:

Facade sealant

Art. no. 0892211, 0892211400, 0892211600, 0892212, 0892212400, 0892212600, 0892213, 0892213400, 0892213600, 0892214, 0892214400, 0892217

EN 15651-1: F-EXT-INT-CC

EN 15651-4: PW-EXT-INT-CC

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Joint sealants for facade elements

EN 15651-1: F-EXT-INT-CC

Joint sealant for footpaths

EN 15651-4: PW-EXT-INT-CC

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Würth International AG

Aspermontstrasse 1

CH – 7000 Chur

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

System 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body Ginger CEPTP (0074) has performed the fire reaction test according to system 3.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1: 2012-12
Volume loss	≤ 10%	
Creep resistance	≤ 3mm	
Adhesive and cohesive properties under pretension after immersion in water (23 °C)	No failure	
Tensile behaviour under pretension at -30°C	No failure	
Durability	Passed	

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	Class E	EN 15651-4: 2012-12
Volume loss	≤ 10 %	
Creep resistance	Passed	
Adhesive and cohesive properties under pretension after storage in water for 28 days	No failure	
Adhesive and cohesive properties under pretension after storage in salt water for 28 days	No failure	
Tensile behaviour under pretension at -30°C	No failure	
Durability	Passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Würth International AG



Gerd Rössler
Managing Director
Chur, 19/06/2014



Patrick Kohler
Head of Power Tools/Material Processing