

DECLARATION OF PERFORMANCE
LE_087506122_01_M_VKP_PREMIUM_PLUS

The present is the version translated from German.
In case of uncertainties, the original in German is considered valid.

1. Unique identification code of the product-type:

VKP PREMIUM PLUS

Art. 087506122, 087506101, 087506152, 087506154, 087506155, 087506156, 087506201, 087506204, 087506209, 0875062511, 0875063018, 087506306, 087509101, 087509152, 087509154, 087509155, 087509156, 087509204, 087509209, 0875092511, 0875093018

2. Intended use/es: **Sealing joints around windows and in building facades**

3. Manufacturer: **Würth International AG
 Aspermontstrasse 1
 CH-7000 Chur**

4. System/s of AVCP: **System 3**

5. European Assessment Document: **EAD 320001-00-0605, March 2016**
 European Technical Assessment: **ETA-22/0401 of 04.07.2022**
 Technical Assessment Body: **Deutsches Institut für Bautechnik, Berlin**

6. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	class E	EAD 320001-00-0605
Driving rain resistance	tight up to 750 Pa; class 9a EN 12208	
Air permeability of joints	$\alpha \leq 1,0 \text{ m}^3 / [\text{h m (daPa)}^{2/3}]$; at least class 4 EN 12207	
Resistance to water vapor diffusion	$\mu \leq 100$	
Resistance to effects of high and low surface temperatures	pass for -30°C to 90° C	
Resistance to the effects of actions of UV radiation in the presence of moisture	pass	
Resistance to heat ageing	pass	
Compatibility with adjoining construction	pass for aluminium, concrete, facing brick, calcareous sandstone, pinewood with coating, pinewood without coating, white PVC or comparable building materials, stainless steel, bare steel, galvanized, zinc, copper, acrylic glass (PMMA), anodized aluminium	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Würth International AG

Managing Director

Product Manager